



SAFE USE INFORMATION SHEET FBS-1 White Glasswool Insulation

Non-Hazardous

Non-Dangerous Goods

SECTION 1: IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	FBS-1 Bradford Black
Other Names:	Bradford Black batts
Product Codes/Trade Names:	N/A
Recommended Use:	Thermal and acoustic insulation, energy conservation and building applications. Used in homes, public and commercial buildings, warehouses and industrial.
Applicable In:	Australia and New Zealand
Supplier:	CSR Building Products Limited ABN 55 008 631 356
Address:	Trinita 3, Level 5, 39 Delhi Road, North Ryde NSW 2113 Australia
Telephone:	+61 2 9235 8000
Email Address:	bradfordwebenq@csr.com.au
Facsimile:	+61 2 9235 8044
Emergency Phone Number:	000 Fire Brigade and Police (available in Australia only)
Poisons Information Centre:	13 11 26 (available in Australia only)

As FBS-1 White Glasswool Insulation products manufactured or sold in Australia and New Zealand by CSR Bradford are classified as **NON-HAZARDOUS**, a Safety Data Sheet (SDS) is not strictly required under Australian Regulations. As such, this Safe Use Information Sheet (SUIS) is issued by CSR Bradford for the information of users, installers and the community. It has been formatted in accordance with the Code on Preparation of a Safety Data Sheets for hazardous chemicals, December 2011, Safe Work Australia (SWA – formerly ASCC/NOHSC).

The information in this SUIS must not be altered, deleted or added to. The Supplier will not accept any responsibility for any changes made to its SUIS by any other person or organization. The Supplier will issue a new SUIS when there is a change in product specifications and/or ASCC standards, codes, guidelines, or Regulations.

SECTION 2: HAZARD IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE:

Classified as **Non-Hazardous** according to the Approved Criteria For Classifying Hazardous Substances [NOHSC: 1008] 3rd Edition. FBS-1 White Glasswool Insulation is classified as **Non-Dangerous Goods** according to the Australian Code for the Transport of Dangerous Goods by Road and Rail in typical installations there will be no identifiable risk to health from these products. Any work area presents hazards, and general safety risks.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name:	Synonyms	Proportion:	CAS Number:
Mineral Glasswool fibre (amorphous, non-crystalline, bio-soluble – Note Q applicable)		>85%	-
Heat-cured binder (fibre binding agent)		<15%	
Mineral oil (solvent-refined dust suppression agent)		<2%	8012-95-1

Note: Traces (<0.1%) of volatile original components of resin may remain in recently manufactured product.

SECTION 4: FIRST AID MEASURES

Swallowed:	Rinse lips and mouth with water.
Eyes:	Flush with clean water. If discomfort persists, seek medical attention.
Skin:	Flush off with water, preferably running. If any itch or discomfort persists, seek medical attention.
Inhaled:	Remove to fresh air. If symptoms persist, seek medical attention.
Advice to Doctor:	Any symptoms and signs of ill-health are likely to be due to other causes. Can be slightly itchy on prolonged contact with skin. Does not produce any acute or chronic health effects. Treatment should be directed toward cleansing the skin and symptomatic treatment as necessary.

SECTION 5: FIRE FIGHTING MEASURES

Flammability:	Non-flammable, will not burn.
Suitable extinguishing media:	As needed for surrounding fire conditions. Any extinguishing media may be used as required. Water fog may be used to cool intact containers and nearby storage areas.
Hazards from combustion products:	FBS-1 White Glasswool Insulation is non-flammable, but the plastic wrapping, resin binder, and some facings may decompose, smolder or burn in a fire. If product is present in a fire, toxic gases or smoke may be evolved depending on surrounding fire conditions.
Fire Fighting Procedures:	As needed for surrounding fire conditions. If required, evacuate area and contact emergency services; remain upwind and notify those downwind of fire hazard; and wear protective equipment including Self-Contained Breathing Apparatus (SCBA).
HAZCHEM Code:	None allocated.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Containment Procedure:	If product is torn or loose, cover or reseal to minimise fibre release. Reuse where possible or place in a sealable plastic bag for disposal according to local authority guidelines.
Clean Up Procedure:	Personnel directly involved in clean-up of loose material should wear personal protective equipment as described in Section 8. Clean area so as to avoid dispersion of loose material.

SECTION 7: HANDLING AND STORAGE

Handling:	<p>These products are safe in use. Once installed, the product does not release dust or fibres.</p> <p>Handling, installing or removing the product may result in some dust and airborne fibre.</p> <p>Minimise eye or skin contact and inhalation during handling, installation and removal (see Section 8). Observe good personal hygiene, including washing hands before eating. Remove personal protective equipment before entering eating areas.</p>
Storage:	<p>Store in original packaging in cool, dry area, removed from foodstuffs. Ensure packages are adequately labeled, protected from physical damage, and sealed when not in use. Avoid packaging being stored under UV light (direct sunlight) for long periods.</p>
Incompatibilities:	None

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

National Exposure Standards:	<p>CSR recommends keeping exposures to dust and other atmospheric contaminants to as low a level as is reasonably practicable. No specific Workplace Exposure Standard (WES) applies to the dust or modified bonded fibre from FBS-1 White Glasswool Insulation products. FBS-1 White Glasswool insulation products manufactured by CSR Bradford are of low biopersistence. Dust from these products is regarded as nuisance dust, and the exposure standard for nuisance dusts of 10 mg/m³, measured as inhalable dust (8-hour TWA*) should be applied.</p> <p>In typical installation conditions or where work is being done on insulated premises, a variety of dusts will be present. In any work area where almost all the airborne material is fibrous FBS-1, then a Workplace Exposure Standard (WES) of 2 mg/m³ (inhalable dust) applies.</p> <p>*An 8-hour time-weighted average (TWA) exposure is the average airborne concentration measured over an eight-hour working day and a 5-day working week.</p>
Notes on Exposure Standards	<p>Exposure Standard (TWA) is the time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life. According to current knowledge this concentration should not impair the health or cause undue discomfort to nearly all workers.</p>
Biological Limit Values:	Not applicable
ENGINEERING CONTROLS	
Ventilation:	<p>During most applications and installation no special ventilation will be required. However, if installing in dusty or poorly-ventilated areas, or during the first heat-up cycle in high-temperature industrial applications, local exhaust ventilation should be considered. Work practices should aim to minimise the release of, and exposure to, fibres and/or dust. Hand tools generate the least amount of dust and fibres. If power tools are used directly on the product appropriate dust collection systems are recommended.</p> <p>Work areas should be cleaned regularly to minimise dust.</p>
PERSONAL PROTECTION EQUIPMENT	
Personal Hygiene	<p>Washing of exposed skin with soap and water at the end of a shift or as required is recommended as a comfort measure.</p>

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION continued	
Skin Protection:	Direct skin contact can be minimised by wearing long-sleeved shirts and long trousers, a cap or hat, and standard duty gloves conforming to Australian Standard AS 2161. Work clothes should be washed regularly and separately from other clothes. Bradford Comfortsleeve™ gloves can also be used as an alternative to long sleeves and gloves.
Eye Protection:	When handling these products, particularly overhead or in enclosed or poorly-ventilated areas such as ceiling spaces or risers, eye contact with dust or fibre can be avoided by wearing ventilated non-fogging dust resistant goggles conforming to Australian and New Zealand Standards AS/NZS 1336.
Respiratory Protection:	None normally required. If dust is generated in enclosed or poorly-ventilated areas, an approved particulate respirator conforming to Australian and New Zealand Standards AS/NZS 1715 and 1716 is recommended. P1, P2 or N95 type respirators are appropriate. Use only respirators that bear the Australian Standards mark and are fitted and maintained correctly, and kept in clean storage when not in use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	A matt of off-white fibrous material resembling cotton wool. It is supplied in different shapes and sizes, in outer packaging. It may be rigid but is typically flexible; and facings such as aluminium foil may be applied to meet specific purposes.
Odour:	Slight sweet odour, particularly when recently manufactured, then odourless
pH, at stated concentration:	Not applicable
Vapour Pressure/Density:	Not applicable
Boiling Point/range (°C):	Not applicable
Melting Point (°C):	>704 °C
Solubility in water:	Insoluble
Specific Gravity (H₂O = 1):	Generally low, but variable depending on facings
Decomposition Temperature	Binder will decompose above 200 °C
Volatile Organic Compounds (VOC) content/Percent Volatiles:	Very low
FLAMMABLE MATERIALS	
Flash Point:	Not applicable
Flash Point Method:	Not applicable
Flammable (Explosive) Limit - Upper:	Not applicable
Flammable (Explosive) Limit - Lower:	Not applicable
Auto-ignition Temperature:	Not applicable

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability:	Stable. The cured binder is stable and will remain intact for the life of the product under normal atmospheric conditions.
Incompatible Materials:	No reported incompatibilities. Acids, alkalis or organic solvents may cause degradation of binder.
Hazardous Reactions/Decomposition Products:	None known

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicology data: –The fibre component of these FBS-1 products is listed by Safe Work Australia as Man-made Vitreous Fibre (Glasswool) of certified low biopersistence as specified under Note Q as listed in the Australian Hazardous Substances Information System and in the Australian Approved Criteria documentation.

In accord with EU ATP 31 (2009) these fibres are not classified as irritant, or as carcinogenic. Previous concerns regarding any health effects from exposure to the fibres from which these products are made, were finally dispelled in 2002 when IARC (part of the World Health Organisation) completed a review of all the health research about FBS-1. The conclusion of IARC was that FBS-1 (including those types used in Australian glasswool, rockwool and slagwool insulation for many decades) was placed in IARC Group 3: not classified as carcinogenic.

Fibres of these products comply with the short-term bio-persistence test and fulfill the requirements of Australian and international authorities on bio-solubility. SWA (formerly ASCC/NOHSC) and international authorities do not classify mineral wool fibres with high bio-solubility as carcinogenic or as capable of causing fibrosis.

Fibres are generally clumped by the binder or resin coating and single strand respirable fibre is present only in trace amounts when any dust is formed in the workplace during installation. Bound fibre is not of respirable size. Extensive research over the past 50 years on workers handling these fibres and products in many countries has shown that the inspirable and respirable size fibres are not harmful, having no long term health effects or respiratory effects.

Toxicology test data is generally not available on the products, but is estimated as being very low with LD50 >5000 mg/kg.

Health Effects: Acute (short-term)

Swallowed:	Unlikely in normal use, but may result in temporary itching of the lips, mouth and throat. Attempting to swallow large amounts would be expected to cause gagging and possibly vomiting.
Eyes:	May cause eye discomfort resulting in watering and redness.
Skin:	Handling repeatedly during installation may cause temporary itching of exposed skin. This is not an allergy, or chemical irritation, and any symptoms usually disappear quickly.
Inhaled:	Unprotected exposure to high levels of dust of these products (during installation or removal) may cause discomfort of the nose, throat, and upper and lower respiratory tract, especially in persons suffering from upper respiratory or chest complaints such as hay fever, asthma or bronchitis.

Note: Products used in high temperature applications (above 200°C) may release fumes from the resin bonding during initial heat-up. In these applications and where suitable protective equipment is not worn (see Section 8), then some irritation to the eyes, nose, throat and respiratory tract may occur. In confined or poorly ventilated areas, use air-supplied respirators during the first heat-up cycle.

Health Effects: Chronic (long-term)

There are no known long-term health effects.

SECTION 12: ECOLOGICAL INFORMATION

Eco-toxicity:	Neither the raw materials nor the finished product contain ozone-depleting chemicals. These products are not classified as hazardous air pollutants. No specific data is available on Eco-toxicity, but estimations based on toxicity information suggest that the materials in these products are not toxic or harmful to fish, birds, insects, wildlife or organisms in the environment.
Persistence and Degradability:	FBS-1 White Glasswool Insulation is bio-soluble and in most eco-systems it would be expected to solubilise over a period of weeks to months. Binder-coated insulation wool is hydrophobic, and no adverse environmental effects would be expected if accidentally released in water or soil.
Ozone Depleting Potential	As referenced in the US EPA list of Ozone Depleting Substances (Class 1 and Class 2), no Ozone Depleting Substances are involved in either the manufacture or composition of this product & therefore has an ozone depletion potential of zero.

SECTION 13: DISPOSAL CONSIDERATIONS

Place in plastic bags or containers and close or seal for disposal in accordance with local authority guidelines. Label as NON-HAZARDOUS insulation wool or as general building waste (non-hazardous), as appropriate to assist local authorities waste disposal sites. Department of Environment and Climate Change NSW classifies all Glasswool insulation as General Solid Waste (non-putrescible), & local authorities will usually advise any local handling arrangements at their disposal sites.

SECTION 14: TRANSPORT INFORMATION

Transport Requirements:	FBS-1 wool insulation are not classified as Dangerous Goods and have no special transport requirements.		
UN number:	None allocated	Subsidiary Risk 1:	None allocated
DG Class:	None allocated	Packaging Group:	None allocated
HAZCHEM code:	None allocated		

SECTION 15: REGULATORY INFORMATION

Poisons Schedule:	Not scheduled. No specific regulatory requirements are applicable regarding occupational health and safety, consumer protection or environmental protection measures.
--------------------------	---

SECTION 16: OTHER INFORMATION

For further information on this product, please contact:	
CSR Bradford Trinity 3, Level 5, 39 Delhi Road, North Ryde NSW 2113	
Phone: 1800 354 044 (available in Australia only)	Fax: 1800 647 260

ADDITIONAL INFORMATION

The following references are intended as guides to good industrial practice applicable to building and construction products.

AS/NZS 1336	Recommended Practices for Occupational Eye Protection
AS/NZS 1715, 1716	Selection, Use and Maintenance of Respiratory Protective Devices
AS 2161	Industrial Safety Gloves and Mittens (excluding electrical and medical gloves)
	OTHER REFERENCES – see next page

AUTHORISATION

Reason for Issue:	New product range
Authorised by:	Peter Ruz
Date of Issue:	06/05/2016

Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of this information.

Other References:

NOHSC:1008 (2004)	Approved Criteria for Classifying Hazardous Substances
Model Code of Practice	Preparation of Safety Data Sheets for Hazardous Chemicals, December 2011, Safe Work Australia.
Model Code of Practice	Labelling of Workplace Hazardous Chemicals, December 2011, Safe Work Australia.
Model Code of Practice	Managing Risks Of Hazardous Chemicals In The Workplace, July 2012, Safe Work Australia.
ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail, 7th edition, National Transport Commission.
WES	Workplace Exposure Standards For Airborne Contaminants, April 2013, Safe Work Australia.
WES	Guidance On The Interpretation Of Workplace Exposure Standards For Airborne Contaminants, April 2013, Safe Work Australia.
GHS	Globally Harmonized System of Classification and Labelling of Chemicals (GHS), 5th revised edition, United Nations, New York and Geneva, 2013.
HSIS	Hazardous Substances Information System (HSIS), internet advisory service, Safe Work Australia.

End of SUIS